

UNIQUE TREAD DESIGN

Excellent self cleaning
Better fuel economy

RAISED CENTER RIBS

Provides better roadability
Higher productivity

CUT & CHIP RESISTANCE TREAD COMPOUND

Resists Stubble Damage
Extensive tire life



FT2 (F2)

BIAS TIRES BUILT FOR TRACTORS



- Specially designed for 2WD tractors in soil tillage and transport applications
- Optimum Land/Sea Ratio for improved traction on and off road
- Strong Casing with Cut/Wear Resistant Compound for higher productivity

Traction



Roadability



Tire Life



Soil Protection



TYRE SIZE

16.0	18.0
5.00-16	7.50-18
6.00-16	20.0
6.50-16	6.50-20
7.50-16	7.50-20
10.00-16	

TECHNICAL DATA

TYRE SIZE	PR	TT / TL	RIM		Unloaded Inflated Dimension		SLR	RC	At Speed 30 kmph (20 mph)			At Speed 40 kmph (25 MPH)			Inflation Pressure		
					SW	OD			Speed Index	Load Index	MAX. LOAD	Speed Index	Load Index	MAX. LOAD			
			Rec. inch	Alt. inch	± 2 % mm	± 2 % mm	mm	± 2.5 % mm			Kgs			Kgs	PSI	Bar	
16																	
5.00-16	6	TT	4.00E	3.00D,4J,4 1/2J	139.7	680.7	330	2032	A6	84	500	A8	76	400	61	4.14	
5.50-16	6	TT	4.00E	3.5D,4.5E	157.5	718.8	330	2133.6	A6	86	530	A8	78	425	54	3.66	
6.00-16 *	8	TT	4.50E	4.00E,4.25KA	159	739	333	2220	A6	94	670	A8	91	615	65	4.5	
6.00-16 *	6	TT	4.50E	4.00E,4.25KA	159	739	333	2220	A6	88	560	A8	85	515	52	3.6	
6.50-16 *	6	TT	4.50E	4.00E,4.25KA	173	761	344.3	2295	A6	91	615	A8	88	560	48	3.3	
7.50-16 *	6	TT	5.50F	6LB	203	808	366	2440	A6	98	750	A8	94	670	44	3	
7.50-16	8	TT	5.50F	6LB	203	808	366	2440	A6	102	875	A8	99	775	56	3.9	
10.00-16 *	10	TL	W8L	8LB	274	894	418	2682	A6	119	1360	A8	111	1090	49	3.4	
18																	
7.50-18	8	TT	5.50F	-	208.3	873.8	406	2616.2	A6	106	950	A8	102	850	56	3.9	
20																	
6.50-20	6	TT	5.00F	4E,5.5F	180.3	863.6	406	2565.4	A6	97	730	A8	93	650	45	3	
7.50-20	6	TT	5.50F	5.0F	205.7	914.4	432	2717.8	A6	103	875	A8	99	775	41	2.78	
7.50-20	8	TT	5.50F	5.0F	205.7	914.4	432	2717.8	A6	108	1000	A8	105	925	56	3.8	

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 – Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM