



STURDY AND ROBUST NYLON CASING

Provides extraordinary impact and shock resistance Extensive tire life

CUT & CHIP RESISTANT TREAD COMPOUND

Ensures resistance against wear and cuts Extensive tire life

UNIQUE TREAD DESIGN

Enables higher traction Better productivity



LT122 (L2)

BIAS TIRES BUILT FOR LOADERS



- Best suited for loading operations
- · Unique inter lug design offers unmatched puncture resistance and durability

TYRE SIZE

24.0

14.9-24

Traction

Tire Life

Ground Stability

Puncture Resistance

1

TECHNICAL DATA

	TYRE SIZE	PR	TT / TL	RIM		Unloaded Inflated Dimension		SLR	RC	At Speed 40 kmph			Inflation
						SW	OD			Speed	Load	MAX. LOAD	Pressure
				Rec. inch	Alt. inch	± 2 % mm	± 2 % mm	mm	± 2.5 % mm	Index	Index	Kgs	PSI
24.0													
	14.9-24	12	TL	DW13	W12	378	1265	570	3800	A8	145.0	2900	42

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other

manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:		