AIR RYDE®



APERTURE SIDEWALL DESIGN

Provides increased driving comfort and heat dissipation Extensive tire life

EXCEPTIONALLY LARGE TREAD DEPTH

Provides high traction in the toughest terrain applications Higher productivity

SPECIALLY ENGINEERED THREE ANGLED STEPPED LUG DESIGN

For exceptional self-cleaning Higher productivity



AIR RYDE

SOLID TWO-STAGE SKID-STEER TIRE



- Non-marker tire available for a clean run on light colored surfaces
- Designed and built to operate in all terrains and challenging conditions
- Engineered to specifically handle extreme lateral forces of skid-steer machines
- Soft cushion ride

Tire Size

31x10-20

33x12-20

Performance

Tire Life

Driving Comfort



TECHNICAL DATA

Tire Size	Rim Size	Profile	Clip on	Tire Dimensions (mm)		Load Capacity at 10 km/h. (kg)	
				Max Width ±1%	OD ± 2%	Load Wheel	Steer Wheel
31x10-20	7.50-20	Air Ryde	•	236	777	4030	3100
33x12-20	7.50-20	Air Ryde	•	287	828	5200	4000

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:			