



## CUT AND TEAR RESISTANT TREAD COMPOUND

Ensures resistance against cuts and chipping Extensive Tire Life

## STURDY AND ROBUST NYLON CASING

Provides extraordinary impact and shock resistance Extensive tire life



# F300 (F3) BIAS TIRES BUILT FOR LOADERS



- Agro Industrial Tire suitable for On & Off road applications
- Strong casing Excellent load caring capacity with long tire life and evenly tread wear

16.0 11L-16SL- 10 11L-16SL- 12

Load Carrying Capacity

**Ground Stability** 

# **TECHNICAL DATA**

	TYRE SIZE	PR	TT/TL	RIM		Unloaded Inflated Dimension		At Speed30 kmph (20 mph)			At Speed40 kmph(25 MPH)			Inflation Pressure
						SW	OD	Speed	Load	MAX. LOAD	Speed	MAX. LOAI	MAX. LOAD	Pressure
				Rec.	Alt.	± 2 %	± 2 %	Index	Index	(KGS.)	Index	Load Index	(KGS.)	PSI
				inch	inch	mm	mm	illuex	IIIuex	(KG3.)	muex		(KG3.)	rəi
16.0														
	11L-16SL	10	TL	8LB	10LB	279	830	A6	116	1250	A8	112	1120	52
	11L-16SL	12	TL	8LB	10LB	279	830	A6	120	1400	A8	116	1250	64

#### **LIMITED WARRANTY**

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other

manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 – Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:			